



1. Access Panel Sizes:

Stylemark Access Panels are specified by the size of the door opening. Stylemark Panels are GFRG (glass fiber reinforced gypsum) for interior applications. Access panel door is a drop in and push out type.

2. Standard Sizes:

| | | Weight: |
|-----------|--------------|---------|
| 9" x 9" | Door Opening | 6 lbs. |
| 12" x 12" | Door Opening | 8 lbs. |
| 16" x 16" | Door Opening | 9 lbs. |
| 18" x 18" | Door Opening | 11 lbs. |
| 24" x 24" | Door Opening | 15 lbs. |
| 22" x 30" | Door Opening | 17 lbs. |
| 30" x 30" | Door Opening | 21 lbs. |

3. Installation:

Stylemark Access Panels are installed with a #6 bugle head screw, joints are taped with standard drywall tape and joint compound. Framing is done by the installer. The Stylemark Panel does not require regular framing, but can be connected to adjacent drywall with studs or blocking.

4. Properties:

Stylemark Access Panel is a glass fiber reinforced gypsum (GFRG) with 1/4" wood imbedded in the frame for fastening and additional strength.

5. Physical Properties:

| | |
|---------------------------------|---------------|
| Shell Thickness | 1/8" to 3/16" |
| Fastener Test Pull Out (Wood) | 525 lbs. Avg. |
| Fastener Test Pull Out (Metal) | 215 lbs. Avg. |
| Fastener Push Through Test | 350 lbs. Avg. |
| Fuel Contribution (ASTM E84-80) | 0 |
| Flame Spread (ASTM E84-80) | 0 |
| Smoke Index (ASTM E84-80) | 0 |
| Combustion (ASTM E84-80) | 0 |
| Class A Non-Rated | 0 |



N5619 Luey Ln. * Plymouth, WI 53073
920-892-8822 * 888-782-5011 * Fax: 920-892-8855
www.iscsupply.com